Technical Solution Sheet 5.10 5: Cold Water Plumbing

Duplicate solution of 1.05, 3.10, 4.03, 6.08, 92.06

Temporary Plumbing for Site Sheds

AIM

The aim of this technical solution is to clarify the requirements for the provision of temporary facilities for site sheds.

COMPLIANCE CERTIFICATES

All plumbing work, including temporary plumbing work must be carried out by a licensed or registered plumbing practitioner. Compliance Certificates must be issued pursuant to 221ZH of the *Building Act 1993* on completion of the plumbing work. The Compliance Certificate should clearly state that the work is temporary.

GASFITTING

In the case of gasfitting, the installation must conform to the requirements of either AS/NZS 5601.1:2013 Gas installations (art 1: General installations or AS/NZS 56012:2:2:5 Part 2: L Gas installations in caravors and boats foresppropulsive purposes as appropriate.

SANITARY DRAINAGE

- Only approved materials can be use
- Only approved fixtures or appliances can be installed.
- The pipework must be joined using normal approved jointing methods, for example any PVC-U pipes and fittings must be joined using primer and solvent cement.
- Wastewater and sanitary discharges can be temporarily connected to the site boundary shaft, inspection shaft or connected into the existing sanitary drainage system.
- Sewer cannot be connected to any stormwater drain.

 Any above ground drains and waste pipes must be protected from construction damage and securely fixed into position.

WATER SUPPLY

- Only approved materials can be used.
- Only approved water heating appliances can be installed.
- The pipework must be able to deliver an acceptable water supply that meets the min mum performance requirements of the Numbing coc of Australia.
- The water supply must have no cross connections and be safe and fit for purpose.

STOR MWATER AND ROOF WORK

- All stormwater and roof work must perform intended purpose.
- Stormwater cannot be connected to any sewerage drain.
- Stormwater from building sites, including any dewatering must comply with local stormwater pollution control laws.

