

# Technical Solution Sheet 1.05

## 1: Sanitary Plumbing

Duplicate solution of 3.10, 4.03, 5.10, 6.08, and 92.06

### Temporary Plumbing for Site Sheds

#### AIM

The aim of this technical solution is to clarify the requirements for the provision of temporary facilities for site sheds.

#### COMPLIANCE CERTIFICATES

All plumbing work, including temporary plumbing work must be carried out by a licensed or registered plumbing practitioner. Compliance Certificates must be issued pursuant to 221ZH of the *Building Act 1993* on completion of the plumbing work. The Compliance Certificate should clearly state that the work is temporary.

#### GASFITTING

In the case of gasfitting, the installation must conform to the requirements of either *AS/NZS 5601.1:2013 Gas installations Part 1: General installations* or *AS/NZS 5601.2:2013 Part 2: LP Gas installations in caravans and boats for non propulsive purposes* as appropriate.

#### SANITARY DRAINAGE

- Only approved materials can be used.
- Only approved fixtures or appliances can be installed.
- The pipework must be joined using normal approved jointing methods, for example any PVC-U pipes and fittings must be joined using primer and solvent cement.
- Wastewater and sanitary discharges can be temporarily connected to the site boundary shaft, inspection shaft or connected into the existing sanitary drainage system.
- Sewer cannot be connected to any stormwater drain.

- Any above ground drains and waste pipes must be protected from construction damage and securely fixed into position.

#### WATER SUPPLY

- Only approved materials can be used.
- Only approved water heating appliances can be installed.
- The pipework must be able to deliver an acceptable water supply that meets the minimum performance requirements of the Plumbing Code of Australia.
- The water supply must have no cross connections and be safe and fit for purpose.

#### STORMWATER AND ROOF WORK

- All stormwater and roof work must perform its intended purpose.
- Stormwater cannot be connected to any sewerage drain.
- Stormwater from building sites, including any dewatering must comply with local stormwater pollution control laws.