

## Building Practice Note FH-01: Building in flood hazard areas

This Practice Note provides guidance on building in a flood hazard area.

The content below provides guidance on

- Identifying an area liable to flooding
- Relevant Victorian variations
- Compliance requirements for building in area liable to flooding

### Abbreviations & Definitions

The abbreviations and definitions set out below are for guidance only. They are not intended to vary those set out in the Building Act 1993, Building Regulations 2018 or the National Construction Code.

- **Act** – Building Act 1993
- **Area liable to flooding** – defined under regulation 5(2).
- **Flood hazard area** – an area liable to flooding within regulation 153.
- **NCC** – National Construction Code 2019
- **RBS** – Relevant Building Surveyor
- **Regulations** – Building Regulations 2018

### Identifying an Area Liable to Flooding

Regulation 5(2) sets out how land may become an area liable to flooding. A building or land that is in an area liable to flooding can be identified through a regulation 51(2) property information request from the council. This information should be obtained at the design stage to ensure that the building will be designed and built above the defined flood level.

Some allotments may also contain a planning overlay relating to flooding such as a Special Building Overlay or a Land Subject Inundation Overlay. In these cases, issues relating to flooding are usually dealt with under the planning schemes and planning permit requirements.

### Report and Consent

Where there is an application for a building permit to construct a building on an allotment that is in an area liable to flooding, regulation 153 requires that a report and consent be obtained from the relevant council. The relevant council will provide design requirements such as the minimum height of the lowest floor.

Regulation 153(1) exempts certain building work from having to obtain a report and consent.



Regulation 153(3) clarifies that a report and consent is not required if the planning permit is required for the construction of the building and the planning scheme regulates the level of the lowest floor of the building.

Similarly, regulation 154 requires that a report and consent of the relevant council must be obtained where there is an application for a building permit to construct a building on designated land or designated works. This ensures the waterway management authority is consulted.

If the consent of the relevant waterway management authority has been obtained as a requirement of a planning permit for the construction of the building, the report and consent of the council does not need to be obtained to an application for a building permit.

## NCC and Regulations

Performance Requirements BP1.4 in NCC Volume One and P2.1.2 in NCC Volume Two, are the relevant Performance Requirements for the design and construction of a building on a site that is in a flood hazard area. The Performance Requirements only apply to Class 1, 2, 3, 4, 9a and 9c buildings.

The relevant Deemed-to-Satisfy Provisions are Vic B1.6 NCC Volume One and 3.10.3.0 in NCC Volume Two which refer the complying with the ABCB Standard for Construction of Building in Flood Hazard Areas’.

Note that the definition of ‘flood hazard area’ and ‘freeboard’ is varied for Victoria.



The Victorian NCC Appendix varies the definition of ‘flood hazard area’ to align with regulation 153 which uses the term ‘area liable to flooding’. Therefore, a reference to ‘flood hazard area’ is to mean an ‘area liable to flooding’ as defined in regulation 5(2).

## ABCB Standard for Construction

The ABCB Standard for Construction of Building in Flood Hazard Areas is available on the ABCB website and is a Deemed-to-Satisfy Solution for areas liable to flooding but is limited to areas where the water maximum flow velocity is not greater than 1.5 m/s. The maximum flow velocity can be determined from Melbourne Water, Water Catchment Authority, or council. If the maximum flow velocity cannot be determined, then the ABCB standard can only be used in inactive flow or backwater areas (defined in the ABCB standard).

Where the ABCB standard cannot be used, a Performance Solution is required to satisfy the Performance Requirements. Alternatively, building modification or determination application can be made to the Building Appeals Board.

## Related Documentation

- Building Act 1993
- Building Regulations 2018
- National Construction Code 2019 Amendment 1
- ABCB Standard for Construction of Building in Flood Hazard Areas

## List of Amendments



- Update format to new VBA style guide.
- Minor amendments to improve readability

## Version History

- Version 1.0, published 24 June 2022, supersedes Practice Note PN 65: Building in Flood Hazard Areas issued 28 June 2018.

## Contact Us

If you have a technical enquiry, please email [technicalenquiry@vba.vic.gov.au](mailto:technicalenquiry@vba.vic.gov.au) or call 1300 815 127.

### **Victorian Building Authority**

Goods Shed North  
733 Bourke Street  
Docklands VIC 3008

[www.vba.vic.gov.au](http://www.vba.vic.gov.au)

## Copyright

© June 2022 Victorian Building Authority (VBA).

This Practice Note has been prepared and published by the VBA for general educational and information purposes only. This publication must not be copied, reproduced, published, adapted, or communicated by any person without the VBA's prior written consent or as permitted by the Copyright Act 1968 (Cth). The VBA makes no warranties or representations whatsoever about the accuracy, reliability, suitability, completeness or authenticity of any information or material contained in this resource. Any use or reliance on such information is at a person's own risk. The VBA accepts no liability whatsoever for any direct, indirect, or consequential loss or damage any person may suffer arising out of or in connection with the access or use of this resource (including any third-party material included in this resource).